

# FGF-800PRO


## **Kings Industrial FGF 3D Printers**

Large Format, High Speed, and Pellets Printing Material











#### **Overview**

Kings FGF-800Pro uses granular and polymer composite materials for printing, which has the advantages of low material cost, fast printing speed and forming speed, high strength, and outdoor weather resistance. It is widely used for sculpture making, furniture designing, mining industry, oil & gas industry, toy industry, art crafts, mold manufacturing, plagues, landscape signs etc.

## Advantage

- Automatic alarm if there is no material
- Emergency stop mode, safety guarantee
- Machine status indicator belt with progress bar
- Integral hoisting, directly used after plugging in
- 12kg closed storage box, pneumatic feeding
- Sensitive touch display screen
- Fully enclosed sheet metal cover for thermal insulation, optional high temperature version

### Ideal Applications

 It is widely used for furniture designing, mining industry, oil & gas industry, toy industry, art crafts, mold manufacturing, plaques, landscape signs etc.



# FGF-800PRO



#### **♦ Technical Data**

Molding technology	Fused granular fabrication
Molding dimensions	(L*W*H) 800*600*800mm
Machine dimensions	(L*W*H) 1130*1030*1632mm
Optional nozzle diameter	0.4-2mm
Nozzle heating method	Two-zone intelligent heating
Storage hopper volume	12kg
Drive mode	Stepper + servo motor
Rated power	3kW
Machine weight	200kg
Working surface temperature	≤120 degrees Celsius
Workbench contact surface	Aluminum Platform/Tempered Glass
The maximum temperature of the nozzle	≤350 degrees Celsius (450 degrees Celsius is optional)
Printing connection method	SD/USB/WiFi
Slicing supported formats	STL/OBJ/AMF/3MF
Compressed air pressure	0.6MPA
Materials	PLA/PETG/ABS/PC/PA/PP/HDPE/TPU/TPV/EVA/PETG+GF/PPS+GF/PA+CF/ABS+CF/PC+CF/PEI+CF etc.
Material particle diameter	1-5mm
Automatic feeder	Integrated
Chamber heating	Option
Power supply voltage	Single-phase AC 220V

