


# 400PRO

## Kings Industrial SLA 3D Printers

23 Innovative Technologies, High Speed SLA 3D Printing  
Efficient and Cost-Effective Prototyping  
Bring Your Idea into Reality



## ◆ Overview

Kings SLA 400Pro 3D Printer provides professional dental 3D digital solutions using model and intraoral 3D scanning technology to collect data, design with professional CAD software, and produce working models, orthodontic models, implant models, guides, wax crowns, and bridges via SLA 3D printing.

## ◆ Advantage

- **Marble Ultra-Stable Main Frame Structure**

The coating reference surface, vertical Z-plane, and optical path fixed plate all use marble structures. The flatness of the guide rail working surface can reach 0.006mm, improving the overall rigidity and stability of the structure.

- **High Scanning Accuracy**

Using a short working distance field lens, the scanning point's working position is more precise, achieving higher dimensional accuracy for printed parts.

- **Compact and Exquisite Appearance**

Smaller XY dimensions and a height reduced by 30cm compared to similar equipment make it suitable for operation in small spaces.

## ◆ Ideal Applications

- Dental Models, Shoe Mold Manufacturing, Jewelry and Accessories, Automotive Parts, Medical Models and Instruments, Scientific Research and Education



## ◆ Technical Data

|                            |                                                                   |
|----------------------------|-------------------------------------------------------------------|
| Printing Size              | 400*400*200mm                                                     |
|                            | 400*400*300mm                                                     |
| First Tank Weight          | 70kg                                                              |
|                            | 100kg                                                             |
| Equipment Dimensions       | 85cm(W)*105cm(D)*190cm(H)                                         |
| Printing Precision         | ±0.08(L≤100mm); ±0.1%*L(L>100mm)                                  |
| Layer Thickness            | Optional (between 0.05mm-0.2mm)                                   |
| Laser Type                 | Diode-Pumped Solid-State Laser Nd, Wavelength 355nm               |
| Beam Size                  | Variable Beam Sizes between 0.08mm-0.8mm                          |
| Scanning System            | High-speed Scanning Galvanometer System, Paired with F-theta Lens |
| Scanning Speed             | 8-15m/s automatically generates scanning paths                    |
| Equipment Control Software | Kings SLA control software, independently developed, copyrighted  |
| Operating System           | Windows 10                                                        |
| Data Interface             | STL, SLC                                                          |
| Power Supply               | 200-240V, 50/60Hz, Unidirectional 10A                             |
| Rated Power Consumption    | 1.2 KVA                                                           |
| Heating Method             | Hot Air Heating (optional)                                        |
| Ambient Temperature        | 20-26°C                                                           |
| Relative Humidity          | ≤40%, Frost-free                                                  |
| Equipment Weight           | 650kg                                                             |



Shenzhen Kings 3D Co., Ltd

- 📍 Building B, No. 148 Huanli Road, Yungu Community, Xinhua Street, Guangming District, Shenzhen, China.
- 📍 No.178, Dingxing Road, High-tech Zone, Zhuhai City, Guangdong Province

Web: [www.kings3dprinter.com](http://www.kings3dprinter.com)

Mob/Whatsapp: +86 17727416895

Email: [market@kings3dprinter.com](mailto:market@kings3dprinter.com)